

LOG, MONITOR, AND OPTIMIZE THE HOT WATER PRODUCTION OF YOUR DUALSUN INSTALLATION

The DualSun T-Box KM2 is a connected monitoring device that tracks the thermal performance of your installation day-by-day.

The T-Box KM2 transports your solar installation to the cloud!


Simply connect to your MyDualSun account and track how your installation is generating free solar hot water!


T-Box KM2 Advantages

- ✓ Provides real-time monitoring of thermal production
- Ensures that installation is performing as expected from MyDualSun simulation report
- ✓ Allows for DualSun technical monitoring and support throughout lifetime of installation

For the installers:

✓ Enables DualSun to adjust settings remotely, minimizing potential on-location maintenance





Technical characteristics

Compatible with all solar controllers equipped with RESOL VBus®*.

Plug & Play installation

MECHANICAL DATA	
Dimensions	95 x 70 x 25 mm
Casing	Plastic
Protection type	IP 20 / IEC 60529
Protection class	III
Ambient temperature	0 40°C
Mounting	Wall

ELECTRICAL DATA	
Mains adapter input voltage	100 240 V~
Nominal current	146 mA
Datalogger input voltage	12 V DC ± 5%

Data interface:

- RESOL VBus® for the connection to the controller
- 10/100 Base TX Ethernet, Auto MDIX, WLAN 2.4~2.4835 GHz



* Examples of compatible controllers: DeltaSol BX Plus, BS Plus, CS, SL, ES, etc...